










## Marine Fuel Rubber ISO7840 A1

Code:RC07112

	 ID	 OD	 WP	 WP	 BP	 BP	 BR	 W/A	 COIL
Inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/m	m
3/16	5	12.5	10	145	30	435	50	150	10-100
1/4	6	13.5	10	145	30	435	60	170	10-100
4/16	8	16.5	10	145	30	435	80	240	10-100
3/8	10	18.5	10	145	30	435	100	280	10-100
1/2	13	22.5	10	145	30	435	130	400	10-100
5/8	16	25.5	10	145	30	435	160	460	10-50
3/4	19	29.5	10	145	30	435	190	640	10-50

<b>Item Code:</b>	<b>RC07112</b>
<b>Tube/Uses:</b>	<b>Black, This tube can be used for Petrol &amp; Diesel oil. It is Resistant NBR Rubber</b>
<b>Reinforcement:</b>	<b>Synthetic Textile</b>
<b>Resistant</b>	<b>This Tube is resistant to Ozone/Weather, Heat, Oil, Flame and sea Conditions.</b>

E: [sales@therubbercompany.com](mailto:sales@therubbercompany.com) W: [www.therubbercompany.com](http://www.therubbercompany.com)