

Experts in Rubber


 $\textit{Manufacturers} \cdot \textit{Designers} \cdot \textit{Distributors}$

Commercial Neoprene Insertion Sheeting - 1 Ply

Product Code: RC0336

Product Description

Our commercial neoprene insertion sheeting is a high-grade 1 ply reinforced material. The combination of neoprene and the fabric insertion creates a material that provides outstanding strength and durability in physically demanding applications. It also offers good resistance against weathering, Ozone, oil and fuel deterioration.



Technical Specification

Properties	Test Method	Values
Product	-	High Grade Neoprene Insertion Sheet- ing
Compound	-	CR/SBR
Hardness (Shore A)	ISO 7619-1	70° ± 5°
Density	ISO 2781	1.40 ±0.05 g/cm ²
Tensile Strength	ISO 37	5 N/mm²
Elongation at Break	ISO 37	300%
Compression Set (22h, 70°C)	ISO 37	35%
Abrasion Resistance	ISO 37	290 mm³
Working Temperature Range	-	-20°C to + 110°C





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Experts in **Rubber**

Manufacturers · Designers · Distributors

Standard Sizes

Properties	Tolerances
0.5mm x 1.4m x 20m	+/- 0.2mm
1mm x 1.4m x 20m	+/- 0.2mm
1.5mm x 1.4m x 10m	+/- 0.3mm
3mm x 1.4m x 10m	+/- 0.3mm
4mm x 1.4m x 10m	+/- 0.4mm
5mm x 1.4m x 10m	+/- 0.4mm
6mm x 1.4m x 10m	+/- 0.5mm
8mm x 1.4m x 5m	+/- 0.7mm
10mm x 1.4m x 5m	+/- 1mm
15mm x 1.4m x 5m	+/- 1mm
20mm x 1.4m x 5m	+/- 1.4mm
25mm x 1.4m x 5m	+/- 1.75mm
32mm x 1m x 1m	
38mm x 1m x 1m	
40mm x 1m x 1m	





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.