

Experts in Rubber

Manufacturers · Designers · Distributors

## Hydrogenated Nitrile Rubber Sheeting HNBR Datasheet Product Code: RC0364

## **Product Description**

Our hydrogenated nitrile HNBR is a premium grade material that offers superior resistance and physical properties compared to our other nitrile material grades. Also known as saturated nitrile, this material is produced by introducing hydrogen into the saturate of the nitrile material. We supply this material in a range of thicknesses from 1mm to 6mm as standard.



## **Technical Specification**

Properties	Test Method	Values
Product	-	Hydrogenated Nitrile Sheeting
Compound	-	NBR
Hardness (Shore A)	ASTM D2240	70° ± 5°
Density	ASTM D297	1.40 g/cm <sup>2</sup>
Tensile Strength	ASTM D412	100 kg/cm²
Elongation at Break	ASTM D412	200%
Tear Strength	ASTM D624	45 kg/cm
Compression Set (22h, 70°C)	ASTM D395 Method B	50%
Working Temperature Range	-	-35°C to + 160°C





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Experts in Rubber

 $Manufacturers \cdot Designers \cdot Distributors$ 

## **Standard Sizes**

Properties	Weight (Kg/m²)
1mm x 1.4m x 20m	1.2
2mm x 1.4m x 20m	2.4
3mm x 1.4m x 10m	3.6
5mm x 1.4m x 10m	6.0
6mm x 1.4m x 10m	7.2





The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.